



Value • Performance • Quality

INFRA-RED CHEESEMELTER/BROILER

MODELS:
TSCMi-24
TSCMi-36
TSCMi-48
TSCMi-60
TSCMi-72
TSCMi-84



TSCMi-24

The Tri-Star Premium Cheesemelter Broiler is fitted with standard features, where considered optional by other manufactures.

Standard features include:

- Heavy duty Atmospheric-Burner for instant even heating.
- Stainless steel top, side panels and front.
- Recessed control valve for easy access & serviceability.
- Continuous pilots with burner control to respond instantly for the need of the hour.
- One year parts and labor warranty.

Design Features:

- Equipped with a heavy-duty removable rack.
- Full width, large capacity broiler pan removes for cleaning.
- Equipped with gas-fired premixed atmospheric infra-red burner that provides instant, even heat. Has adjustable gas valve and continuous pilot for instant lighting.
- Cool to the touch knobs.
- Cheesemelter can be mounted on all TSI Restaurant Ranges using optional heavy-duty reinforcement channels that fit existing back guards.
- Can be counter mounted with optional 4" legs. Can be wall mounted with optional wall mounting brackets.

Options & Accessories

- Additional Racks
- Reinforcement channels for Range mount
- Wall mounting brackets for wall mounting
- 4" legs for counter mounting
- Available in Stainless steel top, bottom and back.

Certifications



Tri-Star Manufacturing • 1307 N. Watters Rd. Suite 180, Allen, TX 75013 • (800) 431.2745

www.tri-starmfg.com

Revised 033016cp



Value • Performance • Quality

INFRA-RED CHEESEMELTER/BROILER

PRODUCT SPECIFICATIONS



Construction:

Stainless steel front and sides. Welded and finished stainless steel seams.

Clearance for counter mounting: for use only on non-combustible surfaces. Provide a 0" clearance from non-combustible surfaces and 4" from combustible surfaces.

Gas Information:

Manifold pressure is 5.0"W.C. for natural gas or 10.0" W.C. for propane gas. Manifold size is 3/4" NPT.

Must specify type of gas and elevation if over 2000 ft. when ordering.

TSCMi-24:

24", 20,000 BTU

TSCMi-36:

36", 35,000 BTU

TSCM-48:

48", 40,000 BTU

TSCMi-60:

60", 55,000 BTU

TSCMi-72:

72", 70,000 BTU

TSCMi-84:

84", 90,000 BTU

Shipping Weight:

TSCMi-24: 112 lbs.

TSCMi-36: 165 lbs.

TSCMi-48: 210 lbs.

TSCMi-60: 277 lbs.

TSCMi-72: 337 lbs.

TSCMi-84: 410 lbs.

Freight Class: 85

