



Value • Performance • Quality

INFRA-RED SALAMANDER/BROILER

MODELS: TSSBi-24
TSSBi-36



TSSBi-24

The Tri-Star Premium Salamander Broiler is fitted with standard features, where considered optional by other manufactures.

Standard features include:

- One 35,000 BTU Atmospheric-Burner for precision instant even heating.
- Heavy gauge steel construction.
- Stainless steel top, side panels and front.
- Recessed control valve for easy access & serviceability.
- Removable heavy-gauge grid carriage with chrome plated wire rack with multi-cooking positions.
- Constant pilot for instant ignition, assigned to each burner.
- Recessed control valve for easy access and serviceability.
- One year parts and labor warranty.

Design Features:

- One piece broiler grid. Chrome-plated and made of heavy bar stock.
- Rack assembly rolls out adequately for loading and unloading. Removes for cleaning.
- Broiler rack has spring balanced, adjustable tension assembly that raises and lowers with positive multi position locking.
- Equipped with gas-fired 35,000 BTU atmospheric infra-red burner.
- Full width, large capacity broiler pan removes for cleaning.
- Range can be mounted on all TSI Restaurant Ranges using optional heavy-duty reinforcement channels that fit existing back guards.
- Can be counter mounted with optional 4" legs. Can be wall mounted with optional wall mounting brackets.

Options & Accessories

- Additional Racks
- Reinforcement channels for Range mount
- Wall mounting brackets for wall mounting
- 4" legs for counter mounting
- Available in Stainless steel top, bottom and back.

Certifications





Value • Performance • Quality

INFRA-RED SALAMANDER/BROILER

PRODUCT SPECIFICATIONS

Construction:

Stainless steel front and sides. Welded and finished stainless steel seams.

Clearance for counter mounting: for use only on non-combustible surfaces. Provide a 0" clearance from non-combustible surfaces and 4" from combustible surfaces.

Gas Information:

Manifold pressure is 5.0" W.C. for natural gas or 10.0" W.C. for propane gas. Manifold size is 3/4" NPT. 3/4".

Must specify type of gas and elevation if over 2000 ft. when ordering.

TSSBi-24:

24" Infra-Red Salamander, 20,000 BTU

TSSBi-36:

36" Infra-Red Salamander, 35,000 BTU

Shipping Weight:

TSSBi-24: 160 lbs.

TSSBi-36: 220 lbs.

Freight Class: 85

